

Liebherr commercial appliances can be found at specialist retailers where providing first-class service and expert advice is their top priority.

You can find an overview of all Liebherr appliances in our catalogues.
Available in stores or on home.liebherr.com.



Smart communication on all fronts



Discover the world of Liebherr-Appliances with the latest interesting news, stories, valuable tips and tricks on food storage, recipes and lots more besides!



Learn all about our current social media channels.
socialmedia.home.liebherr.com



Click the link to directly access our social media channels:
socialmedia.home.liebherr.com

Subject to alterations.



Frozen Food & Ice Cream
2021

Quality, Design and Innovation



Highly efficient and economical: Liebherr freezers

Continuous operation in professional applications puts special demands on freezers for the frozen food and ice-cream industry. That is why Liebherr takes great care in the development of these appliances to meet your customer requirements with high quality and innovative ideas. High-insulating materials, in conjunction with highly efficient compressors, efficient refrigerants, and well-balanced refrigeration components as well as precision electronic

control systems, ensure outstanding refrigeration capacity – even in extreme conditions. In addition, the appliances are easy to clean and very economical in consumption. Company and product brands can be used to stimulate impulse buying. Liebherr offers a wide range of models for almost any application, always featuring premium quality and top design. You can rely on Liebherr professional appliances – 24 hours a day, 365 days a year.

Contents

Increase awareness of your brand	06
Chest freezers	08
Forced-air display freezers	26
Accessories	30
CounterTop appliances	31
Accessories	35

- Climate class definitions
- Climate class 3: Ambient temperatures from +10°C to +25°C
 - Climate class 4: Ambient temperatures from +10°C to +30°C
 - Climate class 5: Ambient temperatures from +10°C to +40°C
 - Climate class 7: Ambient temperatures from +10°C to +35°C

Good reasons to choose Liebherr



Highest performance

Liebherr freezers for the frozen food and ice-cream industries provide full refrigerating capacity even in extreme climate conditions. The use of ultra-modern components, efficient and environmentally friendly refrigerants as well as precision controls ensure that product quality and freshness is preserved – and the appliances are always efficient.

Efficiency

Liebherr freezers operate extremely economically: highly efficient compressors, a precision electronic control system as well as highly effective insulation ensure low power consumption and low operating costs. The high quality of the virtually maintenance-free and service-friendly appliances guarantees long life and reliable operation.

Robust quality

Liebherr appliances are specially constructed for intensive professional use and feature a very sturdy design – with highest-quality materials and perfect workmanship right down to the smallest detail. The quality of the appliances is ensured by elaborate tests. All electronic and refrigeration components are well-balanced to ensure maximum functionality and efficiency – including an attractive design.

Easy cleaning

Hygiene plays an especially important role in the commercial sector. That is why Liebherr upright freezers are equipped with moulded inner liners with large radii that are easy to clean. Height-adjustable wire shelves enable individual adaptation to different packaging types or products.

Product presentation

Attractive product presentation is the best sales support at the point of sale. In Liebherr freezers products are always stored optimally, are within easy reach – and stimulate buying. Large, smooth-running sliding glass lids as well as effective interior lighting enable perfect product display. Excellent product visibility is ensured by the high load line height. Sturdy baskets and adjustable shelves allow perfect adaptation of the storage space to the products stored.

Easy servicing

Liebherr freezers are designed for easy servicing: the generously radiused corners on the moulded inner liners as well as easily removable shelves enable perfect hygiene and save a lot of time. In addition, Liebherr appliances are virtually maintenance-free and very easy to use thanks to their sophisticated concept. All components requiring regular servicing are designed for easy access.

Increase awareness of your brand

Liebherr offers many individual and impressive branding options for freezers. You can choose between various methods and different models. Upon request we can develop customised appliance concepts to meet your specific brand requirements.



Customised vinyls

Depending on the quantity and motif, the desired brand is applied on a suitable vinyl sticker, usually PC film, in a screen printing or digital printing process. Vinyl stickers can be applied by Liebherr in the factory.

Display/side wall/door colours

Customised colour design enables eye-catching presentation of your brand and extremely attractive product display. Different materials and effects can be used to individually design the side walls, the door frames, the handle, the base compartment, the display frame and the inner liner according to customer specifications.



LED logo

An individual motif can be engraved and illuminated with LEDs between the two panes of glass door. The effect is impressive – the motif is showed off brilliantly.



Customised colour design

Customised colour design enables eye-catching presentation of your brand and extremely attractive product display. Different materials and effects can be used to individually design the side walls, the door frames, the handle, the base compartment, the display frame and the inner liner according to customer specifications.



3D effect



3D brand

3D brands give an appliance exceptional appeal and open up completely new possibilities for using images creatively. A special method enables the production of high-quality decals using 3D printing (lenticular method). In addition, we work with different printing levels and layers on the glazing which produce a 3D effect when combined with the right lighting from behind. This way every appliance stands out individually and stimulates impulse buying.

The advantages at a glance



The **energy-efficient LED interior light** creates a powerful visual impact by highlighting the products on display. A lid lock is optionally available.



The **toughened, single-pane safety glass** is shatter-proof, resilient and stabilises the upper area of the chest. Good product visibility is ensured by reduced heat radiation. The lid can be removed for easy handling and cleaning.

Combining **plastic aluminium frame for dimensional stability** with rounded corners for hygienic purpose and user protection in an attractive modern design.



High-performance insulation ensures that temperatures remain even and reduces energy consumption.

RoHS and WEEE conformity by using environmentally friendly materials combined with optimal recyclability.



Sturdy swivel castors make it easier to move the appliance and allow convenient cleaning underneath the appliance.



Sturdy suspended baskets provide a clear view of the goods presented.



Profiled seals allow easy lid opening and closing.



The **steel inner liner** with rounded corners is easy to clean, rust-free, scratch-resistant, enables perfect hygiene and features good thermal conductivity.



The **lid lock** prevents unauthorised access.



Analogue internal temperature display at load-line level with adjustable range between -10 °C and -24 °C to suit individual needs.



Quality right down to the smallest detail

Liebherr chest freezers are specially designed to meet extreme requirements and withstand high stress in professional applications. Sturdy materials, high-quality refrigeration components and quality workmanship guarantee long life. High-impact product

presentation in the chest freezers is ensured by sturdy baskets and sliding glass lids which provide a clear view. In the wide range of sales chest freezers, you will find the right appliance with suitable features for every requirement.



Smooth-running sliding glass lid.
The curved sliding glass lids on the EFI chests are made of toughened, single-pane safety glass. The lid halves are easy to move thanks to profiled seals and the plastic frame heated by hot gas from the compressor.



Insulated sliding lid.
The sliding foam lids range are extremely robust thanks to the composite aluminium and rigid PVC cover. The top is protected with a scratch-resistant aluminium worktop. Insulated sliding foam lid is available as an alternate option to the flat sliding glass lids. A lid lock is available as an accessory.



Maximised total display area.
The slim yet highly durable plastic and aluminium frame provides the greatest possible surface area for displaying merchandise. This means that customers have the best possible view of the freezer's contents and product presentation is optimised.



Stability and design.
Combining plastic parts at the side with connecting aluminium profiles, the cover frame of the EFI and EFE models are very attractive in appearance. The steel inner liner with rounded corners is easy to clean, rust-free and scratch-resistant. Thanks to the steel material, it possesses outstanding thermal conductivity.



High-impact product presentation.
EFI / EFE chest freezers are fitted with a LED interior light that can be switched on separately. The glare-free light is horizontally integrated into the front of the inner liner. Sturdy baskets are available in different sizes for impulse and bulk ice-cream. They can be flexibly arranged to ensure optimum use of the interior. Practical partitions for this purpose are available as an accessory.



Glass canopy.
The robust glass fixture made from toughened safety glass protects ice cream from contamination when selling and helps to ensure goods are presented in an attractive manner. The extra deep front of the glass fixture ensures excellent visibility of products and means that customers always have a good view of the wares presented from a range of different angles. The LED interior lights in appliances EFI 3553 and EFI 4853 also contribute to this. Wafer holders, serviettes and any other of the typical ice cream accessories can be conveniently placed on the fl at shelf area. (Only accessories)



Quieter thanks to outer skin condenser.
Thanks to the foamed in outer skin condenser, the ice-cream chest freezers are virtually maintenance-free – and the housing is easy to clean. In addition, condensation water does not form on the outside.



Sturdy swivel castors.
Swivel castors make transport easier especially when the chest appliances have to be moved frequently. All EFE / EFI models are equipped with high-quality non-marking polyurethane 50-mm swivel castors.



Impulse sales chest freezers

Also available
Models without LED lighting
Total gross / net capacity
Exterior dimensions in mm (w / d / h)
Interior dimensions in mm (w / d / h)
Energy consumption in 365 days ¹
Ambient temperature range
Refrigerant
Sound power level
Connection rating
Frequency / voltage
Cooling system
Defrost
Temperature range
Lid material
External cabinet finish
Internal liner material
Frame colour
Type of control
Temperature display
Interior light
Number of baskets
Number of baskets, max (see picture)
Castors
Lock
Insulation
Water drain
Gross / net weight
Accessories
Basket 270 mm
Basket 210 mm
Partition grid 270 mm / High grid
Partition grid 270 mm / Low grid
Partition grid 210 mm / High grid
Partition grid 210 mm / Low grid
Rubber bumpers, grey
Cylinder lock for glass sliding lid
Glass canopy
Baskets for scoop ice cream containers
Scanner rail

EFI 5653	LED	EFI 4853	LED	EFI 4453	LED
----------	-----	----------	-----	----------	-----

EFI 5603	EFI 4803	EFI 4403
558 / 408 litre	488 / 356 litre	417 / 303 litre
1885 / 680 / 825	1675 / 680 / 825	1465 / 680 / 825
1760 / 535 / 490	1550 / 535 / 490	1340 / 535 / 490
1206 kWh	987 kWh	765 kWh
+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C
R 290	R 290	R 290
52 dB(A)	52 dB(A)	52 dB(A)
2.5 A	2.5 A	2.5 A
50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~
static	static	static
manual	manual	manual
–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C
curved glass slide-lid	curved glass slide-lid	curved glass slide-lid
steel / white	steel / white	steel / white
steel	steel	steel
grey	grey	grey
analogue control	analogue control	analogue control
internal analogue	internal analogue	internal analogue
LED	LED	LED
0	0	0
8	7	6
swivel castors	swivel castors	swivel castors
can be retrofitted	can be retrofitted	can be retrofitted
60 mm	60 mm	60 mm
yes	yes	yes
90.7 / 80.9 kg	89.5 / 79.9 kg	76.4 / 67.4 kg
7111009	7111009	7111009
7111039	7111039	7111039
7111031	7111031	7111031
7111033	7111033	7111033
7111784	7111784	7111784
7111787	7111787	7111787
7266707	7266707	7266707
7043660	7043660	7043660
	9809162	
on request	on request	on request
7652174	7652066	7652065

¹ Measured with light switched off



Impulse sales chest freezers

Also available
Models without LED lighting
Total gross / net capacity
Exterior dimensions in mm (w / d / h)
Interior dimensions in mm (w / d / h)
Energy consumption in 365 days ¹
Ambient temperature range
Refrigerant
Sound power level
Connection rating
Frequency / voltage
Cooling system
Defrost
Temperature range
Lid material
External cabinet finish
Internal liner material
Frame colour
Type of control
Temperature display
Interior light
Number of baskets
Number of baskets, max (see picture)
Castors
Lock
Insulation
Water drain
Gross / net weight
Accessories
Basket 270 mm
Basket 210 mm
Partition grid 270 mm / High grid
Partition grid 270 mm / Low grid
Partition grid 210 mm / High grid
Partition grid 210 mm / Low grid
Rubber bumpers, grey
Cylinder lock for glass sliding lid
Glass canopy
Baskets for scoop ice cream containers
Scanner rail

EFI 3553	LED	EFI 2853	LED	EFI 2153	LED	EFI 1453	LED
EFI 3503		EFI 2803		EFI 2103		EFI 1403	
347 / 250 litre		276 / 197 litre		206 / 145 litre		135 / 91 litre	
1255 / 680 / 825		1045 / 680 / 825		835 / 680 / 825		625 / 680 / 825	
1130 / 535 / 656		920 / 535 / 490		710 / 535 / 490		500 / 535 / 490	
726 kWh		594 kWh		471 kWh		402 kWh	
+10 °C to +35 °C		+10 °C to +35 °C		+10 °C to +35 °C		+10 °C to +35 °C	
R 290		R 290		R 290		R 600a	
52 dB(A)		42 dB(A)		42 dB(A)		42 dB(A)	
1.5 A		1.5 A		1.5 A		1.5 A	
50 Hz / 220 – 240V~		50 Hz / 220 – 240V~		50 Hz / 220 – 240V~		50 Hz / 220 – 240V~	
static		static		static		static	
manual		manual		manual		manual	
–10 °C to –24 °C		–10 °C to –24 °C		–10 °C to –24 °C		–10 °C to –24 °C	
curved glass slide-lid		curved glass slide-lid		sliding glass lid		sliding glass lid	
steel / white		steel / white		steel / white		steel / white	
steel		steel		steel		steel	
grey		grey		grey		grey	
analogue control		analogue control		analogue control		analogue control	
internal analogue		internal analogue		internal analogue		internal analogue	
LED		LED		LED		LED	
0		0		0		0	
5		4		3		2	
swivel castors		swivel castors		swivel castors		swivel castors	
can be retrofitted		can be retrofitted		can be retrofitted		can be retrofitted	
60 mm		60 mm		60 mm		60 mm	
yes		yes		yes		yes	
68.5 / 60.4 kg		61.1 / 53.6 kg		56.3 / 49.6 kg		47.1 / 41.3 kg	
7111009		7111009		7111009		7111009	
7111039		7111039		7111039		7111039	
7111031		7111031		7111031		7111031	
7111033		7111033		7111033		7111033	
7111784		7111784		7111784		7111784	
7111787		7111787		7111787		7111787	
7266707		7266707		7266707		7266707	
7043660		7043660		7043660		7043660	
9809160							
on request		on request		on request		on request	
7652064		7652063		7652062		7652061	

¹ Measured with light switched off



Sales chest freezers	EFE 6052LED	EFE 5152LED	EFE 4652LED	EFE 3852LED
Also available Models without LED lighting				
Total gross / net capacity	593 / 457 litre	519 / 398 litre	444 / 340 litre	369 / 280 litre
Exterior dimensions in mm (w / d / h)	1885 / 680 / 825	1675 / 680 / 825	1465 / 680 / 825	1255 / 680 / 825
Interior dimensions in mm (w / d / h)	1760 / 535 / 523	1555 / 535 / 523	1340 / 535 / 523	1130 / 535 / 523
Energy consumption in 365 days ¹	1112 kWh	910 kWh	751 kWh	620 kWh
Ambient temperature range	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C
Refrigerant	R 290	R 290	R 290	R 290
Sound power level	52 dB(A)	52 dB(A)	52 dB(A)	52 dB(A)
Connection rating	2.5 A	2.5 A	2.5 A	1.5 A
Frequency / voltage	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~
Cooling system	static	static	static	static
Defrost	manual	manual	manual	manual
Temperature range	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C
Lid material	sliding glass lid	sliding glass lid	sliding glass lid	sliding glass lid
External cabinet finish	steel / white	steel / white	steel / white	steel / white
Internal liner material	steel	steel	steel	steel
Frame colour	grey	grey	grey	grey
Type of control	analogue control	analogue control	analogue control	analogue control
Temperature display	internal analogue	internal analogue	internal analogue	internal analogue
Interior light	LED	LED	LED	LED
Number of baskets	0	0	0	0
Number of baskets, max	8	7	6	5
Castors	swivel castors	swivel castors	swivel castors	swivel castors
Lock	can be retrofitted	can be retrofitted	can be retrofitted	can be retrofitted
Insulation	60 mm	60 mm	60 mm	60 mm
Water drain	yes	yes	yes	yes
Gross / net weight	92.1 / 81.9 kg	88.9 / 79.2 kg	76.9 / 70.1 kg	69.3 / 61.2 kg
Accessories				
Basket 270 mm	7111011	7111011	7111011	7111011
Basket 210 mm	7111041	7111041	7111041	7111041
Partition grid 270 mm	7111029	7111029	7111029	7111029
Partition grid 210 mm	7111784	7111784	7111784	7111784
Rubber bumpers, grey	7266707	7266707	7266707	7266707
Cylinder lock for glass sliding lid	7043660	7043660	7043660	7043660
Baskets for scoop ice cream containers	on request	on request	on request	on request
Scanner rail	7652174	7652066	7652065	7652064

¹ Measured with light switched off




Sales chest freezers	EFE 3052LED	EFE 2252LED	EFE 1552LED	EFE 1152LED
Also available Models without LED lighting				
Total gross / net capacity	EFE 3002	EFE 2202	EFE 1502	EFE 1102
Exterior dimensions in mm (w / d / h)	294 / 222 litre	220 / 163 litre	145 / 105 litre	108 / 84 litre
Interior dimensions in mm (w / d / h)	1045 / 680 / 825	835 / 680 / 825	625 / 680 / 825	751 / 481 / 825
Energy consumption in 365 days ¹	920 / 535 / 523	710 / 535 / 523	500 / 535 / 523	605 / 315 / 657
Ambient temperature range	529 kWh	422 kWh	370 kWh	324 kWh
Refrigerant	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C
Sound power level	R 290	R 600a	R 600a	R 600a
Connection rating	42 dB(A)	42 dB(A)	42 dB(A)	42 dB(A)
Frequency / voltage	1.5 A	1.5 A	1.5 A	1.5 A
Cooling system	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~
Defrost	static	static	static	static
Temperature range	manual	manual	manual	manual
Lid material	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C
External cabinet finish	sliding glass lid	sliding glass lid	sliding glass lid	sliding glass lid
Internal liner material	steel / white	steel / white	steel / white	steel / white
Frame colour	steel	steel	steel	steel
Type of control	grey	grey	grey	grey
Temperature display	analogue control	analogue control	analogue control	analogue control
Interior light	internal analogue	internal analogue	internal analogue	internal analogue
Number of baskets	LED	LED	LED	LED
Number of baskets, max	0	0	0	0
Castors	4	3	2	3
Lock	swivel castors	swivel castors	swivel castors	swivel castors
Insulation	can be retrofitted	can be retrofitted	can be retrofitted	can be retrofitted
Water drain	60 mm	60 mm	60 mm	60 mm
Gross / net weight	yes	yes	yes	yes
	61.8 / 54.4 kg	55.1 / 48.4 kg	48.5 / 42.6 kg	42.7 / 39 kg
Accessories				
Basket 270 mm	7111011	7111011	7111011	
Basket 210 mm	7111041	7111041	7111041	
Basket 195 mm				7112788
Partition grid 270 mm	7111029	7111029	7111029	
Partition grid 210 mm	7111784	7111784	7111784	
Partition grid 195 mm				7111712
Rubber bumpers, grey	7266707	7266707	7266707	7266707
Cylinder lock for glass sliding lid	7043660	7043660	7043660	7043660
Baskets for scoop ice cream containers	on request	on request	on request	on request
Scanner rail	7652063	7652062	7652061	7652176

¹ Measured with light switched off



Sales chest freezers	EFE 5100	EFE 4600	EFE 3800	EFE 3000	EFE 2200	EFE 1500
Total gross / net capacity	503 / 449 litre	444 / 382 litre	369 / 316 litre	294 / 251 litre	220 / 186 litre	145 / 120 litre
Exterior dimensions in mm (w / d / h)	1675 / 680 / 840	1465 / 680 / 840	1255 / 680 / 840	1045 / 680 / 840	835 / 680 / 840	625 / 680 / 840
Interior dimensions in mm (w / d / h)	1550 / 535 / 585	1340 / 535 / 585	1130 / 535 / 585	920 / 535 / 585	710 / 535 / 585	500 / 535 / 585
Energy consumption in 365 days	796 kWh	621 kWh	377 kWh	360 kWh	380 kWh	332 kWh
Ambient temperature range	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C	+10 °C to +35 °C
Refrigerant	R 290	R 290	R 290	R 290	R 600	R 600a
Sound power level	52 dB(A)	52 dB(A)	52 dB(A)	42 dB(A)	42 dB(A)	42 dB(A)
Connection rating	2.5 A	2.5 A	1.5 A	1.5 A	1.5 A	1.5 A
Frequency / voltage	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~	50 Hz / 220 – 240V~
Cooling system	static	static	static	static	static	static
Defrost	manual	manual	manual	manual	manual	manual
Temperature range	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C	–10 °C to –24 °C
Lid material	aluminium sliding lid	aluminium sliding lid	aluminium sliding lid	aluminium sliding lid	aluminium sliding lid	aluminium sliding lid
External cabinet finish	steel / white	steel / white	steel / white	steel / white	steel / white	steel / white
Internal liner material	steel	steel	steel	steel	steel	steel
Frame colour	grey	grey	grey	grey	grey	grey
Type of control	analogue control	analogue control	analogue control	analogue control	analogue control	analogue control
Temperature display	internal analogue	internal analogue	internal analogue	internal analogue	internal analogue	internal analogue
Number of baskets	0	0	0	0	0	0
Number of baskets, max	7	6	5	4	3	2
Castors	swivel castors	swivel castors	swivel castors	swivel castors	swivel castors	swivel castors
Lock	can be retrofitted	can be retrofitted	can be retrofitted	can be retrofitted	can be retrofitted	can be retrofitted
Insulation	60 mm	60 mm	60 mm	60 mm	60 mm	60 mm
Water drain	yes	yes	yes	yes	yes	yes
Gross / net weight	87.9 / 75.2 kg	73.2 / 63.4 kg	66.1 / 57 kg	58.5 / 51 kg	52.2 / 47.5 kg	47.8 / 42 kg
Accessories						
Basket 270 mm	7111011	7111011	7111011	7111011	7111011	7111011
Basket 210 mm	7111041	7111041	7111041	7111041	7111041	7111041
Partition grid 270 mm	7111029	7111029	7111029	7111029	7111029	7111029
Partition grid 210 mm	7111784	7111784	7111784	7111784	7111784	7111784
Rubber bumpers, grey	7266707	7266707	7266707	7266707	7266707	7266707
Cylinder lock for foamed lid	7042835	7042835	7042835	7042835	7042835	7042835
Baskets for scoop ice cream containers	on request	on request	on request	on request	on request	on request
Scanner rail	7652066	7652065	7652064	7652063	7652062	7652061

The advantages at a glance



The **cooling condenser** is embedded in the foam insulation all the way round the outer skin, which reduces vibration and makes the appliance quiet in operation. Condensation is stopped from forming on the housing; the outer skin is easy to clean – for perfect hygiene.



Full length recess **handle** allowed user to lift up the door lid at any position. Especially for big unit that can give advantage towards user to lift up the door lid by both hand.

Highly effective insulation prevents energy loss and supports the excellent energy efficiency of the chest freezers. The insulation of the freezers consists of 60-mm-thick, HFC-free polyurethane foam.


The steel **housing** is very sturdy, scratch- and impact-resistant.



The **perfect foaming** of the housing ensures that the chest freezers have the necessary cold reserves even at high ambient temperatures.



The **steel inner liner** with rounded corners is easy to clean and meets hygiene requirements.



The **lock** prevents unauthorised access.



The **main body of the chest** features a very sturdy and rugged design, which ensures that the chests can also withstand intensive loads and are torsion-free.

Stop Frost

The **StopFrost system** reduces frosting on the interior and stored products, so the time-consuming process of defrosting is necessary far less often. The chest can be re-opened effortlessly even after the lid is opened and closed because vacuum does not build up.

Adjustable temperature range between -10°C and -24°C to suit individual needs.



The **analogue temperature display** tells the user the exact internal temperature.

Smooth-running, **swivel castors** with 50-mm wheel diameter are used for excellent manoeuvrability. The stable castors are individually screw-fitted and can be changed without difficulty.



The advantages at a glance



The **display illuminated by energy-efficient LEDs** attracts attention to the appliance and its contents. The display panel can be customised and switched in parallel with the interior light. In addition, specific branding attracts attention to a brand or products. A wide variety of colour options is available for the housing and door frame.

Customised branding options on the display (FDv), on the housing and door frame attract attention to brands or a company and support sales promotion.

The **NoFrost module** is installed behind the display and enables maximum usage of the interior.



The **high-performance forced-air cooling system** rapidly cools down products and maintains a uniform cooling temperature throughout the interior.



The **tough slimline door handle** is ergonomic, easy to grasp and easy to clean.



The **heavy-duty wire shelves** are plastic-coated and have a loading capacity of up to 50 kg. Easy removal at a door opening angle of 90°.



The **moulded inner liner** made of food-safe polystyrol is odourless, very sturdy and durable. It enables perfect hygiene thanks to the generously radiused, easy-to-clean corners.

The natural and **environmentally friendly refrigerant R 290** is CFC free and, in conjunction with highly efficient compressors, very energy-efficient.



FDv 4643

The **highly efficient hot gas defrost system** reduces defrost time to approx. 10 minutes, which distinctly reduces the temperature rise in the appliance. The food quality is preserved for a longer period of time because the products do not have to be removed during the defrost phase and they are not exposed to unnecessary temperature fluctuations.

The **vertical LED lighting mounted on one side** ensures bright illumination of the interior and supports sales promotion with optimum product presentation. Optional for both sides available upon request.

The glass doors with a tough **aluminium frame** have a 90° dwell position allowing easy loading and removal of larger product quantities. At less than 60° the doors close automatically to prevent loss of cold air.


The triple-pane **glass door** prevents **external condensation**.

The air-deflection baffle, mounted in the lower part of the inner liner, deflects the flow of cold air away from the glass door and thus **prevents condensation forming on the outside of the door**. The improved glass door insulation also helps to reduce condensation formation on the door and thereby facilitates optimum product presentation (FDv 4643/Fv 3643).

A special **anti-fog film** significantly delays misting on the inside of the door after opening and closing, to consistently ensure optimum visibility for the products stored (FDv 4643/Fv 3643).

The **digital temperature display** tells the user the exact internal temperature that has been set. The temperature range can be set from -10°C to -25°C using the precision electronic controller.

The **robust lock** prevents unauthorised access.



Optimum product presentation for frozen foods

Attractive product presentation is a crucial condition for drawing the customers’ attention to products. These modern glass door freezers in an attractive anthracite-aluminium design offer real promotional advantages: The interior is fitted with twin side-mounted, vertical LED lighting to create outstanding illumination inside the cabinet. The glass door has a special anti-fog film treatment which significantly delays misting of its inside surface upon opening, to always allow a clear view of the goods. The new integrated air-deflection baffle, together with improved glass door insulation, prevents water condensation forming on the outside of the door thus guaranteeing good visibility of products at all times.



Anti-fog film for improved product visibility
A special anti-fog film significantly delays misting on the inside of the door after opening and closing, to consistently ensure optimum visibility for the products stored.

Lower energy consumption
Thanks to the improved glass door insulation, the energy consumption has been reduced. The triple-pane glass contributes considerably to the freezer’s excellent energy efficiency.



No condensation formation
The air-deflection baffle, mounted in the lower part of the inner liner, deflects the flow of cold air away from the glass door and thus prevents condensation forming on the outside of the door. The improved glass door insulation also helps to reduce condensation formation on the door and thereby facilitates optimum product presentation.



Forced-air display freezers

Total gross / net capacity
Exterior dimensions in mm (w / d / h)
Interior dimensions in mm (w / d / h)
Energy consumption in 365 days ¹
Ambient temperature range
Refrigerant
Sound power level
Connection rating
Frequency / voltage
Cooling system
Defrost
Temperature range
External cabinet finish
Door material
Internal liner material
Type of control
Temperature display
Interior light
Fault: warning signal
Adjustable shelves
Shelf material
Shelf loading
Handle
Castors
Lock
Self-closing door
Door hinges
Insulation
Gross / net weight
Accessories
Baskets, 30 litres
Partition grid for 30-litre basket
Scanner rail 525 mm
Shelf, plastic-coated
Bottom grid, plastic-coated

FDv 4643 Variante E76

No Frost	LED
----------	-----

461 / 307 litre
670 / 721 / 1957
532 / 568 / 1275
1453 kWh
+10 °C to +30 °C
R 290
62 dB(A)
4.4 A
50 Hz / 220 – 240V~
forced-air
automatic
–10 °C to –25 °C
steel / white
glass
commercial grade moulded polystyrol
electronic controller
external digital
LED
visual and audible
4
wire shelves plastic-coated
50 kg
ergonomic slimline handle
2 fixed rear and 2 swivel front castors
fitted
yes
right hand hinged, not reversible
67 mm
154 / 141 kg

Fv 3643 Variante E76

No Frost	LED
----------	-----

365 / 231 litre
690 / 780 / 1688
532 / 730 / 969
1377 kWh
+10 °C to +30 °C
R 290
62 dB(A)
4.4 A
50 Hz / 220 – 240V~
forced-air
automatic
–10 °C to –25 °C
steel / white
glass
commercial grade moulded polystyrol
electronic controller
external digital
LED
visual and audible
3
wire shelves plastic-coated
50 kg
ergonomic slimline handle
2 fixed rear and 2 swivel front castors
fitted
yes
right hand hinged, not reversible
67 mm
136 / 125 kg

¹ Measured with light switched off

Section: Chest freezers

Baskets

Products can be presented in a clearly sorted arrangement with the suspended baskets.



Partition grid

The partition grids for baskets support optimum product presentation and allow flexible organisation of the interior.



Lid lock

A lid lock can be installed on all models to secure the contents of the chest freezers.



Rubber bumpers

Rubber bumpers can be fixed to provide better ventilation when freezers are placed next to each other and to avoid damages during moving.



Glass fixture

The robust glass fixture made from toughened safety glass protects ice cream from contamination when selling and helps to ensure goods are presented in an attractive manner. The extra deep front of the glass fixture ensures excellent visibility of products and means that customers always have a good view of the wares presented from a range of different angles. The LED interior lights in appliances EFI 3553 and EFI 4853 also contribute to this. Wafer holders, serviettes and any other of the typical ice cream accessories can be conveniently placed on the flat shelf area.



Wire basket for scoop-ice containers

The sturdy wire baskets for scoop-ice containers are specially configured for the EFI/EFE chest freezers. Containers can be optimally arranged in the wire baskets so that ice-cream is perfectly presented and conveniently set out for selling by the scoop.



Section: Forced-air display freezers

Baskets

These heavy-duty baskets have capacities of 30 litres.



Partition grid for baskets

The partition grids for baskets support optimum product presentation and allow flexible organisation of the interior.



Scanner rail 525 mm

Price tags and scan codes can easily be read off the practical scanner rail, which is fastened to the front of the shelves. The paper inserts can be used for pricing, branding or other useful customer information.



Shelves

The plastic-coated grid shelves are height-adjustable and allow variable use of the interior for different frozen products. The close-mesh grid shelves have an extremely high loading capacity and ensure secure positioning of the products.



Base-grid, plastic-coated

A sturdy, plastic-coated base-grid ensures optimum use of the appliance base. The base-grid protects the inner liner from damage and ensures secure product storage.



For frozen display without compromise

Liebherr's compact yet spacious CounterTop appliances enhance your sales where space is limited. In bars, restaurants or on sales counters – the Liebherr CounterTop appliances attract impulse purchases of beverages and ice creams. They combine the flexible use of storage space, bright and efficient LED lighting and maximum product visibility. Customised

colour schemes and unique branding possibilities ensure the focus is on what's most important - the products for sale. Low energy consumption, compact design, flexible use and robust build-quality are also good reasons to choose Liebherr CounterTop appliances.



Vertical LED interior light.
Ideal for the attractive product presentation. The LED light column is integrated in the side wall and ensures attractive illumination. The focus is therefore always on the products.



Temperature display.
The LED temperature display is integrated in the front panel of the CounterTop Fv 913. The temperature can be precisely set and clearly displayed.



Fan-assisted cooling.
On the CounterTop appliances BCv 1103 and Fv 913, highly efficient fans ensure that contents are frozen or cooled rapidly, guaranteeing uniform temperature distribution throughout the entire interior. Liebherr's dynamic cooling system is a huge advantage during events when appliances are frequently restocked.



Door profiles, recessed grip, replaceable gaskets.
Aluminium door profiles with a continuous recessed grip are not only elegant, they also make the door easier to open. The replaceable door gasket adds to the efficient operation. It can easily be inserted, cleaned or replaced, thus enabling perfect hygiene.



Replaceable door hinge.
The CounterTop appliances are right hand hinged as standard and can be changed to the left if necessary. They can be adapted on site to suit each location.



Wire shelves.
The plastic-coated grid shelves are height-adjustable in 15 mm increments and the interior can be arranged and used in a variable manner depending on the size of the products. This means the customers always have easy access to the contents. The shelves are close-meshed for even small items and extremely resilient so that products are always stored securely. There is also a bar across the front of the shelf to prevent items falling out.

Section: CounterTop appliances

Stacking kit

To make best use of the available space, with the stacking kit the CounterTop appliances Fv 913 and F 913 can be combined on top of, or next to one another.



CounterTop appliances		
	Fv 913 Premium Freezer	F 913 Freezer
	No Frost LED	LED
Total gross / net capacity	93/66 litre	93/77 litre
Exterior dimensions in mm (w/d/h)	497/558/816	497/558/816
Interior dimensions in mm (w/d/h)	417/391/611	377/430/611
Energy consumption in 365 days ¹	1008 kWh	811 kWh
Ambient temperature range	+10 °C to +35 °C	+10 °C to +30 °C
Refrigerant	R 290	R 290
Sound power level	60 dB(A)	50 dB(A)
Connection rating	1.5 A	1.5 A
Frequency / voltage	50 Hz/220–240V~	50 Hz/220–240V~
Cooling system	forced-air	static
Defrost	automatic	manual
Temperature range	–10 °C to –25 °C	–10 °C to –25 °C
External cabinet finish	steel / silver	steel / silver
Door material	glass door	glass door
Internal liner material	steel	steel
Type of control	electronic controller	analogue control
Temperature display	external digital	internal analogue
Interior light	LED light column on right	LED light column on right
Fault: warning signal	visual and audible	
Adjustable shelves	2	2
Shelf material	wire shelves plastic-coated	wire shelves plastic-coated
Shelf loading	30 kg	30 kg
Handle	recessed grip	recessed grip
Lock	fitted	fitted
Self-closing door	yes	yes
Door hinges	right, reversible on site	right, reversible on site
Insulation	60 mm	60 mm
Gross / net weight	47.8 / 45.3 kg	47.8 / 45.3 kg
Accessories		
Set of connection elements, left, white	9875023	9875023
Set of connection elements, right, white	9875025	9875025
Set of connection elements, left, silver	9875167	9875167
Set of connection elements, right, silver	9875197	9875197
Scanner rail	7444051	7444051
Shelf, plastic-coated	7113033	7113035